

ESD0017PV-00

#### **ENVIROSENSOR**

# **Recon Series**

**Real-Time Monitoring for Mission-Critical Operations** 





**Environment Monitoring** 

Automatic Event Notification



Event & Data Logging

Web Interface Management

CyberPower ENVIROSENSOR assists the administrator to ensure the environment is operated in appropriate condition by providing accurate readings of temperature and humidity, and by monitoring connected devices, e.g. door sensor and security switch, through four dry contacts.

## **TECHNICAL SPECIFICATIONS**

| Model   | ENVIROSENSOR            |
|---|-------------------------|
| Management & Communications                           |                         |
| Connector Type  | RJ45                    |
| Input Dry Contact                                     | 4                       |
| Measurement Range & Accuracy                          |                         |
| Temperature Measurement (°C)                          | 0 ~ 70                  |
| Temperature Accuracy (°C)                             | ± 1                     |
| Relative Humidity Measurement<br>(Non-condensing) (%) | 10~90                   |
| Relative Humidity Accuracy<br>(Non-condensing) (%)    | ± 2%                    |
| Physical  |                         |
| Dimensions (WxHxD) (mm.)                              | 45 x 29 x 59            |
| Weight (g.)   | 41.5                    |
| Shipping Dimensions                                   |                         |
| Dimensions (WxHxD) (mm.)                              | 168 x 58 x 164          |
| Weight (g.)   | 279.5                   |
| Certifications  |                         |
| Certifications  | CE, FCC Class B, C-Tick |
| RoHS  | Yes                     |

#All specifications are subject to change without notice. ©2017 Cyber Power Systems, Inc. All Trademarks are the property of their owners.

## APPLICATIONS

- Office, SOHO Office
- **Back Office**
- Server Room
- Data Center
- Remote House
- Supermarket
- Hospital
- Factory

## SERIES FEATURES

- Real-time Temperature and Humidity Readings
- Monitor up to 4 Connected Devices through a **Dry Contact Interface**
- Easy Access by a Web Browser
- Automatic Event Notification via Email, SNMP Traps, Syslog and SMS
- Work with CyberPower RMCARD

